

Model LP55E

POT WASHER WITH DOUBLE SKIN CABINET



Specially designed stainless steel, indented anti-clog wash arms, easily removed for cleaning, without tools • Pressed molded wash tank with radial corners and double filters for hygiene and easy maintenance • Insulated double skin cabinet construction reduces energy costs, noise levels and keeps the wash area ambient temperature, to an absolute minimum • Large 22.6 x 24.6 in basket with 24.6 in wash height suitable for washing trays, gastronorm containers GN1/1 530x325 mm, bakery trays 600x400 mm, baskets, etc • Rinse booster pump • High efficiency, self draining wash pump for greater hygiene and ultimate washing power • Peristaltic rinse aid dosing

Technical Characteristics



Pot Washer (Art.-Nr. 206700)

LP57E

Digital control panel with display temperatures and functions	(sec.)	Baskets/h	Trays/h
Wash cycle I *	75	48	432
Wash cycle II *	120	30	270
Wash cycle III *	180	20	180
Wash cycle IV * (on going)	600	6	54
Dimensions (W x D x H closed hood / open hood)	27.2 x 28.5 x 66.3 / 73 in		
Clear entry height	24.6 in		
Basket size	22.6 x 24.6 in		
Wash pump power	1,42 kW		
Tank element / boiler element * load switching	3 kW / 6 kW		
Total power / Voltage *	7,42 kW / 208/230 Volt 3-N-PE 60 Hz		
Water supply temperature / water supply pressure / hardness water	max. 131°F / 30 - 60 PSI / min. 7 max. 12° F **		
Inlet water connection / drain / max. h drain	R ¾" / 1" ¾ / 13 in		
Wash temperature / Rinse temperature	131°C / 185° F		
Tank capacity / Boiler capacity / Water consumption per cycle	9.2 gl / 2.3 gl / 0.79gl		
Pump capacity	170 gl/min		

Features and accessories

Auto-self draining wash pump	●
Double wash tank filters	●
Pressed molded wash tank with radial corners	●
Powerful anti-clog wash arms and contra-rotating light weight rinse arms	●
Peristaltic rinse aid dosing	●
Water supply pipe, drain pipe, main power cable	●
Door auto-start micro switch	●
Double skin cabinet	●
Rinse booster pump (PR)	●
Digital control panel with display temperatures (Tronic)	●
Drain pump (PS)	○
Internal water softener (A) (max. 20°dF)	○
Detergent dosing (PD)	○
Break tank (B)	○
Salt low warning lamp	○
Steam condenser unit and heat recovery (STS)	○
Equipment	1 universal, 1 of 9 trays

* theoretical production & power with water supply at 50°C ** above 12° F we suggest a water softener

● = standard ○ = on demand